



# Specification Sheet

# BoneDamp™

2034-C Van Buren Ave. • Indian Trail, NC 28079 • Phone: 704.334.8222

**BoneDamp™** Dampproofing Membrane is a modified asphalt emulsion developed for use as a below grade dampproofing barrier. **BoneDamp™** has low vapor permeance and good adhesion. Typical uses for **BoneDamp™** include dampproofing, residential poured foundations and crawl spaces.

**BoneDamp™** is spray applied and will completely cure in 2 to 6 hours.

## Technical Data

Type	Asphalt emulsion with polymer modification
Color	Black
Solids	62% ± 2%
Density	8.3 lbs/gal
Application	Airless spray
Application Temperature	Minimum 10°F
Application Thickness	60-65 sf/gal for 16 mil (dry) application
Cure Time	2 - 6 hrs

For more application  
information visit

[www.drydogbarriers.com](http://www.drydogbarriers.com)

or email us

[info@drydogbarriers.com](mailto:info@drydogbarriers.com)

## Applications

- Poured Foundations
- Pre-Cast Foundations
- Retaining Walls
- Cavity Wall Air Barrier

The information and recommendations discussed in this publication are believed to be correct. However, this should not be accepted as a guarantee of their accuracy, and confirming test should be run in your own plant or laboratory. No statement should be construed as a recommendation for any use, which would violate any patent rights. Nothing contained herein shall constitute a warranty with respect to the products described or their use.

BoneDamp™  
Issue: A  
Revision: 1  
Date: 01/18/07