

Specification Sheet BoneDry™ RP

2034-C Van Buren Ave. • Indian Trail, NC 28079 • Phone: 704.334.8222

BoneDry™ RP Waterproofing Membrane is a modified asphalt emulsion developed for use as a below grade waterproofing barrier. **BoneDry™ RP**'s low vapor permeance, outstanding adhesion, and superior combination of hardness and flexibility make it a great choice for any below grade waterproofing application. Some typical applications include waterproofing residential basements and crawl spaces.

BoneDryTM RP is spray applied and can instantly build virtually any thickness¹ your job demands. Instant thickness means you can install the remainder of your waterproofing system immediately after the product has been sprayed - no additional trips to complete waterproofing because your membrane isn't cure.

Property	Test Method	Value	Fo
Color		Black/Brown	www
Non Volatile Solids		63% ± 2%	
Density		8.3 lbs/gal.	info@
Coverage Rate		22-25 sq. ft./gal.	
Thickness		40 mil (Dry)	
Elongation	ASTM D-412	> 500%	
Tensile Strength	ASTM D-412	22 psi	
Adhesion to Concrete	ASTM C-836	Exceeds	
Water Degradation	ASTM D-2939	No Degradation	
Water Vapor Permeance	ASTM E-96 Wet	0.0267 gr/hr*sq.ft.	
Mold Growth & Bacterial Attack	ASTM D-3273, 3274	No Degradation	
Low Temp Flexibility	ASTM C-836	No Cracking	
Crack Bridging	ASTM C-836	No Loss of Adhesion	
Hardness	ASTM C-836	75	

For more application information visit

www.drydogbarriers.com or email us info@drydogbarriers.com

Applications

- Poured Foundations
- Retaining Walls
- Cavity Wall air barrier
- Seamless Flashing



BoneDry™ RP waterproofing membrane shown with available12" DrainMax™ foundation strip drain to make the BD1000 Waterproofing System

BoneDry™RP

¹ To obtain recommended thickness this product must be used with BoneDry™ Accelerator.