



Specification Sheet

FasTape SRA-W

2034-C Van Buren Ave. • Indian Trail, NC 28079 • Phone: 704.334.8222

Description:

Low Density Polyethylene Film Tape - 9.0 mil - Synthetic Rubber Based Adhesive remains permanently tacky and bonds well to most surfaces over a wide range of temperatures; excellent low temperature bond. Tough polyethylene backing offers good abrasion and tear resistance. Highly conformable, waterproof and resistant to chemical deterioration. 3" Core.

Color:

White

Format:

4" X 36 yd

Applications:

Ideal for polyethylene splicing; patching / repairing poly sheeting used in boating and RV industry; surface protection & electroplate masking; wire identification; packaging; etc. Works well in most applications where a low thread count polyethylene coated cloth tape is being used.

Physical Properties:

Total Thickness	9.0 mil (0.229mm)
Tensile Strength	22 lbs/inch width
Elongation	100%
Adhesion to Steel	60 oz/inch
Adhesion to Backing	35 oz/inch
Moisture Vapor Transmission	0.4 grams/100 sq. in./24 hrs.

For more application
information visit
www.drydogbarriers.com
or email us
info@drydogbarriers.com

The information and recommendations discussed in this publication are believed to be correct. However, this should not be accepted as a guarantee of their accuracy, and confirming test should be run in your own plant or laboratory. No statement should be construed as a recommendation for any use, which would violate any patent rights. Nothing contained herein shall constitute a warranty with respect to the products described or their use.

FasTape SRA-W
Issue: A
Revision: 1
Date: 08/23/05